

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (original): A bed for detecting shift of a position of a bedded person on a bedding surface, comprising:

a first pressure sensitive sensor and a second pressure sensitive sensor each having a cable shape, disposed separately along side edges of the bedding surface at both end sides in a width direction of the bedding surface, respectively, each of which detects an acceleration component caused by a movement of a bedded person; and

determination means which compares output signals from the first pressure sensitive sensor and the second pressure sensitive sensor to determine a shift state of the bedded person toward a side portion of the bedding surface.

Claim 2 (original): A bed according to claim 1, wherein the first pressure sensitive sensor and the second pressure sensitive sensor are arranged in a manner that a wiring density on a head portion side of the bedded person is set to be higher than other region.

Claim 3 (currently amended): A bed according to claim 1-~~or~~-2, wherein the first pressure sensitive sensor and the second pressure sensitive sensor are arranged in a manner that a wiring density on a leg portion side of the bedded person is set to be lower than other region.

Claim 4 (currently amended): A bed according to claim 2-~~or~~-3, wherein the first pressure sensitive sensor and the second pressure sensitive sensor are wired in a wave shape on the bedding surface, and the wiring density is changed in accordance with an interval between adjacent waves of the wave shape.

Claim 5 (currently amended): A bed according to claim 1 ~~one of claims 1 to 4~~, wherein projection pieces are disposed on an upper side or a lower side of the pressure sensitive sensor and are overlapped on the pressure sensitive sensor at plural portions thereof.

Claim 6 (original): A bed according to claim 5, wherein the pressure sensitive sensor is adhered to a sheet and the projection pieces are adhered to a sheet, and the pressure sensitive sheet to which the pressure sensitive sensor is adhered and the projection piece sheet to which the projection pieces are adhered are laminated to each other.

Claim 7 (currently amended): A bed according to claim 1 ~~one of claims 1 to 6~~, wherein the determination means outputs a notification signal when it is determined that positional shift of the bedded person on the bedding surface arises, and notification means is further provided which notifies occurrence of shift in response to the notification signal outputted from the determination means.

Claim 8 (original): An in-bed detection method of a bed for detecting shift of a position of a bedded person on a bedding surface, comprising the steps of:

obtaining a ratio between intensities of output signals from a first pressure sensitive sensor and a second pressure sensitive sensor each having a cable shape, disposed separately along side edges of the bedding surface at both end sides in a width direction of the bedding surface, respectively, each of which detects an acceleration component caused by a movement of a bedded person; and

determining that positional shift of the bedded person on the bedding surface arises when the ratio is in a predetermined range set in advance.

Claim 9 (original): A bed comprising:  
at least one of a back raising panel portion and a knee raising panel portion;

driving means which performs elevational driving of at least one of the back raising panel portion and the knee raising panel portion,

a side fence;

a pressure sensitive sensor which is disposed at an entire periphery or a part of a surface end portion of at least one of the back raising panel portion and the knee raising panel portion;

determination means which determines touch of a bedded person to the pressure sensitive sensor based on an output signal from the pressure sensitive sensor; and

control means which controls the driving means in accordance with a determination signal from the determination means.

Claim 10 (original): A bed according to claim 9, wherein the pressure sensitive sensor is formed by a non-linear flexible member which displacement amount with respect to a load is non-linear and a piezoelectric sensor with flexibility which deforms according to a displacement of the non-linear flexible member.

Claim 11 (original): A bed according to claim 10, wherein the non-linear flexible member is configured by a thin type elastic material which is formed in a belt shape and has a convex portion.

Claim 12 (currently amended) : A bed according to claim 10-~~or 11~~, wherein the non-linear flexible member and the piezoelectric sensor are disposed in deformation means capable of deforming according to a load.

Claim 13 (original) : A bed according to claim 12, wherein the deformation means has a hollow portion so that at least one of the non-linear flexible member and the piezoelectric sensor can be deformed easily.

Claim 14 (currently amended) : A bed according to claim 9 ~~one of claims 9 to 13~~, wherein that the determination means determines whether or not a bedded person continues to touch the pressure sensitive sensor based on an output signal from the pressure sensitive sensor.

Claim 15 (currently amended) : A bed according to claim 9 ~~one of claims 9 to 14~~, wherein the control means is arranged to validate the determination signal from the determination means when the driving means performs the elevational driving and to invalidate the determination signal from the determination means when the driving means does not perform the elevational driving.

Claim 16 (original): A bed pad comprising:  
a low-repulsion urethane layer; and  
a pressure sensitive sensor disposed on a lower  
surface of the low-repulsion urethane layer.

Claim 17 (original): A bed pad comprising:  
a low-repulsion urethane layer;  
a cushion lawyer made of usual urethane disposed on a  
lower surface of the low-repulsion urethane layer; and  
a pressure sensitive sensor disposed on a lower  
surface of the cushion lawyer.

Claim 18 (currently amended): A bed pad according to  
claim 16 ~~or 17~~, wherein the pressure sensitive sensor is  
configured by a cord-shaped piezoelectric sensor with  
flexibility.

Claim 19 (currently amended): A bed comprising:  
a rigid plate having unevenness formed on a surface  
thereof; and  
a bed pad which is disposed on the rigid plate and  
recited in claim 16 ~~one of claims 16 to 18~~.

Claim 20 (original): A bed comprising:  
a bed frame;

Appl. No. TBD

Preliminary Amdt. Dated December 15, 2005

Reply to Office action of N/A

a movable plate attached on the bed frame so as to be able to incline; and

a bed element which is disposed on the movable plate and recited in claim 19.